

AD/L2030-5W

## Panel Light 5W H.P.F



### Specifications

| MODEL NO.                  | AD/L2030-5W3000K            | AD/L2030-5W-4K              | AD/L2030-5W                 |
|----------------------------|-----------------------------|-----------------------------|-----------------------------|
| COUNTRY OF ORIGIN          | Saudi Arabia                | Saudi Arabia                | Saudi Arabia                |
| INPUT VOLTAGE. FREQUENCY   | 220-240V, 50/60Hz<br>/45VDC | 220-240V, 50/60Hz<br>/45VDC | 220-240V, 50/60Hz<br>/45VDC |
| IP                         | 20                          | 20                          | 20                          |
| LUMINOUS FLUX              | 340lm                       | 340lm                       | 340lm                       |
| EFFICACY                   | 68lm/W                      | 68lm/W                      | 68lm/W                      |
| POWER                      | 5W                          | 5W                          | 5W                          |
| BEAM ANGLE                 | 100°                        | 100°                        | 100°                        |
| POWER FACTOR               | 0.9                         | 0.9                         | 0.9                         |
| LIFE TIME                  | 30,000h                     | 30,000h                     | 30,000h                     |
| COLOR TEMPERATURE          | 3000K                       | 4000K                       | 6500K                       |
| NUMBER OF SWITCHING CYCLES | 15000                       | 15000                       | 15000                       |
| CRI                        | >80                         | >80                         | >80                         |
| NON-DIMMABLE LIGHT         | Yes                         | Yes                         | Yes                         |
| LAMP TYPE                  | Directional                 | Directional                 | Directional                 |
| COLOR CONSISTENCY          | <6                          | <6                          | <6                          |
| LUMEN MAINTENANCE          | ≥80%                        | ≥80%                        | ≥80%                        |
| INSTANT FULL LIGHT         | Yes, < 1s                   | Yes, < 1s                   | Yes, < 1s                   |
| AMBIENT TEMPERATURE        | -10°C to +50°C              | -10°C to +50°C              | -10°C to +50°C              |
| APPLICATION                | Indoor use                  | Indoor use                  | Indoor use                  |
| LAMP DIMENSIONS            | Ø75mm                       | Ø75mm                       | Ø75mm                       |

AD/L2030-6.5W

## Panel Light 6.5W H.P.F



### Specifications

| MODEL NO.                  | AD/L2030-6.5W-3K  | AD/L2030-6.5W-4K  | AD/L2030-6.5W     |
|----------------------------|-------------------|-------------------|-------------------|
| COUNTRY OF ORIGIN          | Saudi Arabia      | Saudi Arabia      | Saudi Arabia      |
| INPUT VOLTAGE. FREQUENCY   | 220-240V, 50/60Hz | 220-240V, 50/60Hz | 220-240V, 50/60Hz |
| IP                         | 20                | 20                | 20                |
| LUMINOUS FLUX              | 455lm             | 455lm             | 455lm             |
| EFFICACY                   | 70lm/W            | 70lm/W            | 70lm/W            |
| POWER                      | 6.5W              | 6.5W              | 6.5W              |
| BEAM ANGLE                 | 90°               | 90°               | 90°               |
| POWER FACTOR               | >0.9              | >0.9              | >0.9              |
| LIFE TIME                  | 30,000h           | 30,000h           | 30,000h           |
| COLOR TEMPERATURE          | 3000K             | 4000K             | 6500K             |
| NUMBER OF SWITCHING CYCLES | 15,000            | 15,000            | 15,000            |
| CRI                        | >80               | >80               | >80               |
| NON-DIMMABLE LIGHT         | Yes               | Yes               | Yes               |
| LAMP TYPE                  | Directional       | Directional       | Directional       |
| COLOR CONSISTENCY          | <6                | <6                | <6                |
| LUMEN MAINTENANCE          | ≥80%              | ≥80%              | ≥80%              |
| INSTANT FULL LIGHT         | Yes, < 1s         | Yes, < 1s         | Yes, < 1s         |
| AMBIENT TEMPERATURE        | -10°C to +50°C    | -10°C to +50°C    | -10°C to +50°C    |
| APPLICATION                | Indoor use        | Indoor use        | Indoor use        |
| LAMP DIMENSIONS            | Ø123mm            | Ø123mm            | Ø123mm            |

## Panel Light 15W H.P.F

AD/L2030-15W



### Specifications

| MODEL NO.                  | AD/L2030-15W3000K        | AD/L2030-15W-4K          | AD/L2030-15W             |
|----------------------------|--------------------------|--------------------------|--------------------------|
| COUNTRY OF ORIGIN          | Saudi Arabia             | Saudi Arabia             | Saudi Arabia             |
| INPUT VOLTAGE. FREQUENCY   | 220-240V, 50/60Hz /45VDC | 220-240V, 50/60Hz /45VDC | 220-240V, 50/60Hz /45VDC |
| IP                         | 20                       | 20                       | 20                       |
| LUMINOUS FLUX              | 1125lm                   | 1125lm                   | 1125lm                   |
| EFFICACY                   | 75lm/W                   | 75lm/W                   | 75lm/W                   |
| POWER                      | 15W                      | 15W                      | 15W                      |
| BEAM ANGLE                 | 104°                     | 104°                     | 104°                     |
| POWER FACTOR               | 0.9                      | 0.9                      | 0.9                      |
| LIFE TIME                  | 30,000h                  | 30,000h                  | 30,000h                  |
| COLOR TEMPERATURE          | 3000K                    | 4000K                    | 6500K                    |
| NUMBER OF SWITCHING CYCLES | 15000                    | 15000                    | 15000                    |
| CRI                        | >80                      | >80                      | >80                      |
| NON-DIMMABLE LIGHT         | Yes                      | Yes                      | Yes                      |
| LAMP TYPE                  | Directional              | Directional              | Directional              |
| COLOR CONSISTENCY          | <6                       | <6                       | <6                       |
| LUMEN MAINTENANCE          | ≥80%                     | ≥80%                     | ≥80%                     |
| INSTANT FULL LIGHT         | Yes, < 1s                | Yes, < 1s                | Yes, < 1s                |
| AMBIENT TEMPERATURE        | -10°C to +50°C           | -10°C to +50°C           | -10°C to +50°C           |
| APPLICATION                | Indoor use               | Indoor use               | Indoor use               |
| LAMP DIMENSIONS            | Ø145mm                   | Ø145mm                   | Ø145mm                   |

## Panel Light 22W H.P.F

AD/L2030-22W



### Specifications

| MODEL NO.                  | AD/L2030-22W01-3K        | AD/L2030-22W01-4K        | AD/L2030-22W01           |
|----------------------------|--------------------------|--------------------------|--------------------------|
| COUNTRY OF ORIGIN          | Saudi Arabia             | Saudi Arabia             | Saudi Arabia             |
| INPUT VOLTAGE. FREQUENCY   | 220-240V, 50/60Hz /68VDC | 220-240V, 50/60Hz /68VDC | 220-240V, 50/60Hz /68VDC |
| IP                         | 20                       | 20                       | 20                       |
| LUMINOUS FLUX              | 1650lm                   | 1650lm                   | 1650lm                   |
| EFFICACY                   | 75lm/W                   | 75lm/W                   | 75lm/W                   |
| POWER                      | 22W                      | 22W                      | 22W                      |
| BEAM ANGLE                 | <120°                    | <120°                    | <120°                    |
| POWER FACTOR               | >0.9                     | >0.9                     | >0.9                     |
| LIFE TIME                  | 30,000h                  | 30,000h                  | 30,000h                  |
| COLOR TEMPERATURE          | 3000K                    | 4000K                    | 6500K                    |
| NUMBER OF SWITCHING CYCLES | 15000                    | 15000                    | 15000                    |
| CRI                        | ≥80                      | ≥80                      | ≥80                      |
| NON-DIMMABLE LIGHT         | Yes                      | Yes                      | Yes                      |
| LAMP TYPE                  | Directional              | Directional              | Directional              |
| COLOR CONSISTENCY          | <6                       | <6                       | <6                       |
| LUMEN MAINTENANCE          | ≥80%                     | ≥80%                     | ≥80%                     |
| INSTANT FULL LIGHT         | Yes, < 1s                | Yes, < 1s                | Yes, < 1s                |
| AMBIENT TEMPERATURE        | -10°C to +50°C           | -10°C to +50°C           | -10°C to +50°C           |
| APPLICATION                | Indoor use               | Indoor use               | Indoor use               |
| LAMP DIMENSIONS            | Ø231mm                   | Ø231mm                   | Ø231mm                   |