

AD/L4001

## STREET LIGHT (LED INTEGRATED)



## Specifications

Model No.	AD/L4001-50W	AD/L4001-100W	AD/L4001-150W
Voltage-Frequency	100-265Vac - 50/60Hz	100-265Vac 50/60Hz	100-265Vac 50/60Hz
Toal Lumens	4750lm	9500lm	14250lm
Efficiancy	95 lm/W	95 lm/w	95lm/w
Beam Angle	75°	75°	75
Power	50W	100W	150W
Power Factor	0.9	0.9	0.9
Long Life	30000h	30000h	30000h
Light Type	Direct	Direct	Direct
CRI	≥ 80	≥ 80	≥ 80
Lumen Maintinance	≥ 80%	≥ 80%	≥ 80%
Instant On	Yes	Yes	Yes
Number of Switching Cycles	15,000 Cycles	15,000 Cycles	15,000 Cycles
Non-Dimmable Light	Yes	Yes	Yes
Color Temp.	7000K <input checked="" type="checkbox"/> 3000K <input type="checkbox"/>	7000K <input checked="" type="checkbox"/> 3000K <input type="checkbox"/>	7000K <input checked="" type="checkbox"/> 3000K <input type="checkbox"/>



## When the lamp is broken



Place the residue in a tightly sealed bag and then discard it securely.



Clean the broken light residues.



Avoid cleaning by hand or touching the skin.



Ventilate the place well for between five and ten minutes.

**The lamp does not contain any hazardous substances.**